



SIRME SI CABLURI SA

ZINC- ALUMINIUM (95%/5%) STEEL WIRE ROPES, CLASS A

NR. CRT.	CONSTRUCTION	CORE			TENSILE STRENGTH N/ mm ²
		IWRC	WSC	FC	
		Diametru mm			
SIMPLE CONSTRUCTION ROPES					
1	1 x 7	/	2 - 6 mm	/	1570-1770
2	1 x 19	/	3 - 10 mm	/	1570-1770
3	1 x 37	/	4 - 14 mm	/	1570-1770
DOUBLE CONSTRUCTION ROPES, NORMAL CONSTRUCTION					
4	6 x 7	4 - 18 mm	4 - 18 mm	4 - 18 mm	1570-1770
5	6 x 19M	5 - 30 mm	5 - 30 mm	5 - 30 mm	1570-1770
6	6 x 37M	7 - 42 mm	7 - 42 mm	7 - 42 mm	1570-1770
DOUBLE CONSTRUCTION ROPES, FLEXIBLE CONSTRUCTION					
7	6 x 30 + 7FC	/	/	6 - 30 mm	1570-1770
8	6 x 24 + 7FC	/	/	8 - 36 mm	1570-1770
9	6 x 12 + 7FC	/	/	12 - 42 mm	1570-1770
DOUBLE CONSTRUCTION ROPES, COMBINED CONSTRUCTION, SEALE AND WARRINGTON-SEALE					
10	6 x 19S	8 - 25 mm	/	8 - 25 mm	1570-1770
11	6 x 26WS	8 - 27 m	/	8 - 27 mm	1570-1770
12	6 x 36WS	10 - 34 mm	/	10 - 34 mm	1570-1770
13	6 x 31WS	10 - 31 mm	/	10 - 31 mm	1570-1770
14	6 x 31S	9 - 30 mm	/	9 - 30 mm	1570-1770
15	6 x 41WS	12 - 40 mm	/	12 - 40 mm	1570-1770
16	4 x 36WS	14 - 26 mm	/	12 - 26 mm	1570-1770
DOUBLE CONSTRUCTION ROPES, COMBINED CONSTRUCTION, FILLER AND WARRINGTON					
17	6 x 19F	10 - 27 mm		10 - 27 mm	1570-1770
18	6 x 19W	8 - 26 mm		8 - 26 mm	1570-1770
NONROTATING ROPES					
19	18 x 7	/	6 - 30 mm	8 - 32 mm	1570-1770
20	18 x 19	/	8 - 48 mm	14 - 40 mm	1570-1770
21	18 x 19S	/	22 - 40 mm	22 - 40 mm	1570-1770
22	35(W) x 7	/	12 - 40 mm	/	1570-1770
DOUBLE CONSTRUCTION ROPES, NORMAL, CONCENTRIC, NONROTATING, FILLER, SEALE AND WARRINGTON-SEALE, WITH 8 STRANDS					
23	8 x 7	6 - 20 mm	6 - 20 mm	6 - 20 mm	1570-1770
24	8 x 19	8 - 36 mm	8-36 mm	8 - 36 mm	1570-1770
25	8 x 37	14 - 50 mm	14 - 50 mm	14 - 50 mm	1570-1770
26	8 x 19W	8 - 32 mm	/	8 - 32 mm	1570-1770
27	8 x 19S	10 - 28 mm	/	10 - 28 mm	1570-1770
28	8 x 19F	14 - 34 mm	/	14 - 34 mm	1570-1770
29	8 x 31WS	14 - 36 mm	/	14 - 36 mm	1570-1770
30	8 x 36WS	14 - 42 mm	/	14 - 42 mm	1570-1770
31	8 x 41WS	22 - 46 mm	/	22 - 46 mm	1570-1770