



SIRME SI CABLURI SA
ZINC- ALUMINIUM (95%/5%) STEEL WIRE ROPES CLASS B

NR. CRT.	CONSTRUCTION	CORE			TENSILE STRENGTH N/ mm ²
		IWRC	WSC	FC	
		Diametru mm			
SIMPLE CONSTRUCTION ROPES					
1	1 x 7	/	2 - 6 mm	/	1570-1960
2	1 x 19	/	3 - 10 mm	/	1570-1960
3	1 x 37	/	4 - 14 mm	/	1570-1960
DOUBLE CONSTRUCTION ROPES, NORMAL CONSTRUCTION					
4	6x 7	4 - 18 mm	4 - 18 mm	4 - 18 mm	1570-1960
5	6 x 19M	5 - 30 mm	5 - 30 mm	5 - 30 mm	1570-1960
6	6 x 37M	7 - 42 mm	7 - 42 mm	7 - 42 mm	1570-1960
DOUBLE CONSTRUCTION ROPES, FLEXIBLE CONSTRUCTION					
7	6x30+7FC	/	/	6-30 mm	1570-1960
8	6x24+7FC	/	/	8-36 mm	1570-1960
9	6x12+7FC	/	/	12-42 mm	1570-1960
DOUBLE CONSTRUCTION ROPES, COMBINED CONSTRUCTION, SEALE AND WARRINGTON-SEALE					
10	6x19S	8-25 mm	/	8-25	1570-1960
11	6x26WS	8-27 mm	/	8-27	1570-1960
12	6x36WS	10-34 mm	/	10-34	1570-1960
13	6x31WS	10-31 mm	/	10-31	1570-1960
14	6x31S	9-30 mm	/	9-30	1570-1960
15	6x41WS	12-40 mm	/	12-40	1570-1960
16	4x36WS	14-26 mm	/	12-26	1570-1960
DOUBLE CONSTRUCTION ROPES, COMBINED CONSTRUCTION, FILLER AND WARRINGTON					
17	6x19F	10-27 mm		10-27 mm	1570-1960
18	6x19W	8-26 mm		8-26 mm	1570-1960
NONROTATING ROPES					
19	18x 7	/	6-30 mm	8-32 mm	1570-1960
20	18x19	/	8-48 mm	14-40 mm	1570-1960
21	18x19S	/	22-40 mm	22-40 mm	1570-1960
22	35(W)x7	/	12-40 mm	/	1570-1960
DOUBLE CONSTRUCTION ROPES, NORMAL, CONCENTRIC, NONROTATING, FILLER, SEALE AND WARRINGTON-SEALE, WITH 8 STRANDS					
23	8x7	6-20	6-20	6-20	1570-1960
24	8x19	8-36	8-36	8-36	1570-1960
25	8x37	14-50	14-50	14-50	1570-1960
26	8x19W	8-32	/	8-32	1570-1960
27	8x19S	10-28	/	10-28	1570-1960
28	8x19F	14-34	/	14-34	1570-1960
29	8x31WS	14-36	/	14-36	1570-1960
30	8x36WS	14-42	/	14-42	1570-1960
31	8x41WS	22-46	/	22-46	1570-1960